
LAMINATED GLASS

- Impact Safety-Rated: Complies With IBC Requirements for Use in Doors. Meets ANSI Z97.1 Class A and CPSC 16CFR 1201 (CAT I and II)
- 1/4" Thick Laminated Architectural Glass
- Comprised of Two Plies of Glass and a .030" PVB Interlayer
- Manufactured in USA
- NON Fire-Rated
- STC 35 Rating



POLYCARBONATE HIGH IMPACT

- Impact Safety-Rated: Complies With IBC Requirements for Use in Doors. Meets ANSI Z97.1 Class A and CPSC 16CFR 1201 (CAT I and II)
- Burglary-Resisting Material. Meets UL Standard 972
- Available in 1/4", 1/2" Thicknesses (Specify on Order)
- Colorless Transparent Sheet
- Virtually Unbreakable 300 Times Stronger Than Ordinary Glass
- Unlikely to Shatter or Chip When Bombarded With Thrown Rocks, Bricks or Bottles.
- UV Stabilized to Resist Solar Exposure
- Manufactured in USA
- 5-Year Manufacturer Warranty
- NOT Fire-Rated
- ◆ Acoustical Ratings: 1/4" = STC 29

1/2" = STC 34

Thicknesses Available

1/4"
1/2"