
## PYRAN<sup>®</sup> PLATINUM F fire-protective safety glass ceramic

- ♦ 3/16" (5mm) Thick Glass Ceramic
- Heavy-Duty 7 Mil Durable Safety Film
- Neutral Coloration Clear and Wireless
- Advanced Manufacturing Process Eliminates the Need for Surface Polishing
- Etched With UL Classification on Each Piece
- 10-Year Manufacturer Warranty
- Weight: 2.5 Lbs./Sq. Ft.
- STC 31 Rating

## **Fire-Rating Information:**

- Certified by UL to ANSI/UL 9, ANSI/UL10B, ANSI/UL10C, CAN/ULC-S104, ULC CAN4-S106 With Closed Cell PVC
  Foam Glazing Tape Like NGP L-GT-116, L-GT-118, or L-GT-132
- IBC Applicable Edition May Limit Maximum Size Allowable



Rating	Application	Max. Visible Glass Area (Sq. Inches)	Max. Width Visible Glass	Max. Height Visible Glass
20, 45, 60, 90 Minute	Doors* (Non-Temp Rise)	3,708	37 3/4"	981/4"
20, 45, 60, 90 Minute	Side-Lites, Borrowed Lites, Transom Lites	4.933	981/4"	981/4"
180 Minutes	Doors* Including Temp-Rise	100	12"	33"

\*With Fire-Rated Glass Lite Kit

## Impact Safety Rating Information:

Meets ANSI Z97.1, Class A

Meets CPSC 16CFR 1201 (Category I and II)

Complies With IBC Requirements for Use in Doors, Side-Lites, Transom Lites and Borrowed Lites.